

INSTALLATION

TEF 7250 CABLE CLAMP

SAFE AREA

Subject to change without prior notice TPS2062 REV. B 30.06.2017



Tranbergs cable clamps are all designed for use in rough environments. Installation equipment manufactured by Tranberg is delivered to offshore installations, oil tankers and supply ships, hotels and hospitals all over the world.

TECHNICAL DATA

Material:	AISI 316L
Thickness:	2,0, 2,5 and 3,0 mm
With:	16,0 mm
Hole diameter:	7,0 mm

APPLICATION

- Cable clamping in harsh industrial environments

FEATURES AND BENEFITS

- Made of acid resistant stainless steel SS316L
- Strong and solid construction
- Manufactured in different sizes for 1 or 2 cables
- Rugged and low profile

APPROVALS AND CERTIFICATES

NA

TEF 7250 CABLE CLAMPS

DESCRIPTION

Part No.	Cable diam.		No. of cables	Length (approx)	Width	Thickness	Weight per. 100	Normal packages
	Min.	Max						
7250 002	8mm	11mm	1	30mm	16mm	2,0mm	0,9 kg.	100 pcs.
7251 002	11mm	14mm	1	36mm	16mm	2,0mm	1,1 kg.	100 pcs.
7252 002	10mm	12mm	2	40mm	16mm	2,5mm	1,6 kg.	100 pcs.
7271 002	14mm	18mm	1	40mm	16mm	2,5mm	1,5 kg.	100 pcs.
7272 002	12mm	17mm	2	48mm	16mm	2,5mm	1,9 kg.	100 pcs.
7281 002	18mm	22mm	1	50mm	16mm	2,5mm	1,8 kg.	100 pcs.
7282 002	15mm	20mm	2	54mm	16mm	2,5mm	2,3 kg.	100 pcs.
7296 002	22mm	27mm	1	53mm	16mm	2,5mm	2,5 kg.	100 pcs.
7297 002	27mm	32mm	1	63mm	16mm	3,0mm	3,2 kg.	50 pcs.
7298 002	32mm	38mm	1	64mm	16mm	3,0mm	3,7 kg.	50 pcs.

SUPPORT FOR CABLE CLAMPS

Part No.	Dimensions		Width	Thickness	Weight per 100	Normal package
	Length	Height				
7299 002	60mm	18mm	16mm	3,0mm	3,0 kg.	100 pcs.

ILLUSTRATIONS

