DEN HAAN ROTTERDAM is proud to present its DHR73. A signalling light which satisfies all the demands of long service life, low energy consumption and wide range of possible applications.

Needless to say that the DHR73 meets all RPR / BPR and Colreg standards. With this light DEN HAAN Rotterdam proves yet again that going beyond the standard technical requirements is worth the effort.

Application

- General signalling purposes.
- Vessels carrying dangerous cargos.
- Vessels of official guards.
- Fire fighting vessels.

Electrical specification

- Voltage 90 up to 265VAC and 24VDC +/- 20%. Remark: both voltages can be connected at the same time.
- Consumption 7,5 12Watt (adjustable).
- According IEC 60598-2-1, conform directives 73/23/EEC and 93/68/EEC.

· Operation temperature

- -25 up to 55°C.

Optical

- Visibility 3 5 N.m. (blue 2 N.m.).
- Light intensity and colour specification, according to the new European standard EN 14744.

Adjustable signal

- Continuously.
- 30, 60, 120, 180 flashes p/m.

Lifetime

- Approx. 50.000 hours.
- Protection class
- IP67.

Materials

- Chromatted aluminium.
- Well glass, borosilicate, ø64 x ø49 x 73mm.
- Power supply, encapsulated.

- 3 layers of UV-resistant powder coating, white RAL9016.

Cable gland

- M25, cable diameter 6-13mm.

Mounting

Triangular base, 3 fixing slots ø7,5mm.



Manufacturer of navigational lighting, search lights, ship's horns & decorative nautical lamps

DEN HAAN ROTTERDAM MARINE ACCESSOIRIES

Fascinatio Boulevard 1182 - 2909 VA Capelle a/d IJssel PO Box 84176, 3009 CD Rotterdam - The Netherlands T +31 10-413 0755 - F +31 10-413 5487 - E sales@dhr.nl ISO 9001:2000 Certified - Member

www.dhr.nl



TPS4145

DHR73

WITH LED TECHNOLOGY