

TRANBERG® LIGHTING

HML-ISO LED 5 Daylight Signalling Lamp

Safe Area



The new HML-ISO LED 5 offers you unbeatable advantages which not only facilitate operating and maintenance but also convince in handling and security at the same time.

Quote from the SOLAS (Safety of Life at Sea) (1997) Regulations: "all ships of over 150 tons gross tonnage, when engaged on International voyages, shall have onboard an efficient daylight signalling lamp which shall not be solely dependant upon the

ship's main source of electrical power."

Application

- The handheld signalling light can be used on all vessels, for ship to ship signalling using Morse Code.
- HML-ISO LED 5 can also be used as a torch light due to its continuous light function

Features and benefits

- Toughened front glass
- Rubber sealing
- Quick fastening rubber
- LED
- Connection cable =5m
- SOS function
- Permanent light function
- This device is built at least according to requirements of DNV
- ABS carrying case with battery
- Battery Charger
- Red, green and blue filters included
- 2 flush mount power outlets included

Approvals and certificates

DNV GL SE MEDB00007XN



Technical Data

Protection class to EN 60 529:	IP56
Material housing:	Fibre Reinforced Polyamide
Material Globe/Diffuser:	Polycarbonate
Color:	Black
Voltage:	12 / 24 V
Wattage:	5W
Signal-range:	Day: 4 km Night: 18 km
Lamp:	LED
Light color:	Constant
Average lamp life:	10,000 h
Tamb:	-25 -to +55 °C

TRANBERG

STAHL

THE STRONGEST LINK.

R. STAHL TRANBERG AS

Main office | Strandsvingen 6 | N-4032 Stavanger, Norway | T +47 51 57 89 00 | E info.no-st@r-stahl.com | stahl-tranberg.com

TRANBERG® LIGHTING

HML-ISO LED 5 Daylight Signalling Lamp

Safe Area

Description	Dimensions	Weight	Part No.
HML-ISO LED 5 Daylight Signalling Lamp w/ carrying case	525 x 435 x 220 (mm)	12 kg.	2519225500

Accessories	Weight	Part No.
Power outlet, 10A, IP56, Flush mounting. For hand held signalling light	0,2 kg.	2519225101
Power outlet, 10A, IP56, Bulkhead mounting. For hendheld signalling light	0,3 kg.	2519225102

Dimensions

