

# RULES FOR COLREG 72, PART C RULE 27 VESSELS NOT UNDER COMMAND OR RESTRICTED IN THEIR ABILITY TO MANOUVRE

Subject to change without prior notice TTP3300 REV. A 11.07.2017

## Not under command



**Rule 27**

## Restricted ability to manoeuvre



**Rule 27**

## RULE 27 A, B, C, AND H

### (a) A vessel not under command shall exhibit:

- (i) two all-round red lights in a vertical line where they can best be seen;
- (ii) two balls or similar shapes in a vertical line where they can best be seen;
- (iii) when making way through the water, in addition to the lights prescribed in this paragraph, sidelights and a sternlight.

### (b) A vessel restricted in her ability to maneuver, except a vessel engaged in mineclearance operations, shall exhibit:

- (i) three all-round lights in a vertical line where they can best be seen. The highest and lowest of these lights shall be red and the middle light shall be white;
- (ii) three shapes in a vertical line where they can best be seen. The highest and lowest of these shapes shall be balls and the middle one a diamond.

(iii) when making way through the water, [a masthead light or lights/ masthead lights], sidelights and a stern light in addition to the lights prescribed in subparagraph (b)(i);

(iii) when at anchor, in addition to the lights or shapes prescribed in subparagraphs (b)(i) and (b) (ii), the light, lights, or shapes prescribed in Rule 30.

(c) A power-driven vessel engaged in a towing operation such as severely restricts the towing vessel and her tow in their ability to deviate from their course shall, in addition to the lights or shapes prescribed in [Rule 24(a) / subparagraph (b)(i) and (ii) of this Rule], exhibit the lights or shape prescribed in [subparagraph (b)(i) and

(ii) of this Rule / Rule 24].

(h) The signals prescribed in this Rule are not signals of vessels in distress and requiring assistance. Such signals are contained in Annex IV to these [Regulations / Rules].

# RULES FOR COLREG 72, PART C - RULE 27 VESSELS NOT UNDER COMMAND OR IN RESTRICTED IN THEIR ABILITY TO MANOUVRE

## RECOMMENDED EQUIPMENT

### VESSELS 7 - 20 METERS

Description	Lantern type		Colour	Weight	Part No.
Lantern 2898 AL	All-round	360°	White	0,84 kg.	2898 500
Lantern 2898 AL	All-round	360°	Red	0,84 kg.	2898 700

### VESSELS MORE THAN 20 METERS

Lantern 2870 A	All-round	360°	White	2,85 kg.	2870 510
Lantern 2870 AR	All-round	360°	Red	2,85 kg.	2870 710
Lantern 2870 A	1/2 All-round	181°	White	2,85 kg.	2870 511
Lantern AR	1/2 All-round	181°	Red	2,85 kg.	2870 711
Lantern 2870 A, 230V, signal light only	1/2 All-round	181°	White	2,85 kg.	2870 513
Lantern 2870 AR, 230V, signal light only	1/2 All-round	181°	Red	2,85 kg.	2870 713